



BLOCK "D" ROOF PLAN




BLOCK "H" ROOF PLAN

NOTES


1. All Fall Prevention Anchorages (FPA's) to comply with AS1891, and must be installed in accordance with manufacturer's recommendations.
2. All fixed ladders, stairways and platforms to comply with AS1657.
3. All designated access points to be restrictable, include signage in accordance with AS1319, and have a single anchor point located within 1 metre.
4. All roof access hatches to be lockable and open away from fall hazard.
5. All ladder access brackets to prevent movement in vertical and horizontal planes.

THIS ROOF ACCESS SAFETY SYSTEM IS DESIGNED FOR THE USE OF SAFEMASTER ENERGY ABSORBING ANCHORS ONLY

THE USE OF ANY OTHER PRODUCT MAY MEAN THAT THE BUILDING STRUCTURE MUST BE STRENGTHENED



TIMBER ANCHOR DETAIL



STEEL ANCHOR DETAIL

LEGEND

+	TYP. ANCHOR POINT
LAB	TYP. LADDER BRACKET
⇦	DIRECTION OF TRAVEL BETWEEN ANCHOR POINTS
←	DIRECTION OF ROOF FALL
☒	ROOF ACCESS HATCH

PROJECT KINGSWAY CHRISTIAN COLLEGE - 157 KINGSWAY, DARCH W.A.

DATE	SCALE	DRAWN	DRAWING No.
AUGUST '05	1 : 200	S.W.	2761

Safemaster SAFETY PRODUCTS
P.O. Box 1373, Canning Vale 6970
45-47 Willenberg Drive, Canning Vale W.A. 6155
Telephone: (08) 9456 5666
Fax: (08) 9456 5014
ABN 20 461 467 196

© This remains the property of Safemaster Safety Products