

TEST CERTIFICATE

ANCHOR POINT PERFORMANCE



Safemaster certifies that **X-ERT Surface Mount Anchor Kit (Code: APS205)** is designed, manufactured and tested in accordance with **AS/NZS 5532:2013** subject to installation of roof deck and anchor point in accordance with manufacturer's requirements



Test Identification

068/033

Tested Item

APS205 - X-ERT Surface Mount Anchor

Tested Item Descriptions

With Energy Absorbing Swivel Attachment Point
15kN Rated/Single Person Use
Universal Plate

Test Type

Dynamic & Static Test to AS/NZS 5532:2013

Roof Sheet Type

Kliplock

Roof Sheet (BMT)

0.42mm

Purlin Spacing

1500mm

Anchor Load Limit

15kN Ultimate Load (Single Person Free Fall Arrest)

Minimum Fixings

7x Bulbtite 7.7x27.7 Aluminium Rivets, 2x 14g 10x75mm Screws

Date Certificate Is Prepared

18/09/2014

DISCLAIMER

Product designed as a single point anchor device used for harness based work. Any change made to the roof deck design, material composition or installation method will void this certification. All Safemaster products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Safemaster requirements or the use of non Safemaster components will void all certification and warranties. Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a structural engineer or a site specific live load test done to ensure conformance. Maintenance and usage of the system in accordance with Safemaster requirements is the responsibility of the owner or manager of the workplace. Safemaster takes no responsibility for the misuse of or tampering with this Height Safety Equipment or its use by untrained personnel.

TEST CERTIFICATE

ANCHOR POINT PERFORMANCE



Safemaster certifies that **X-ERT Surface Mount Anchor Kit (Code: APS205)** is designed, manufactured and tested in accordance with **AS/NZS 5532:2013** subject to installation of roof deck and anchor point in accordance with manufacturer's requirements



Test Identification

075/144

Tested Item

APS205 - X-ERT Surface Mount Anchor

Tested Item Descriptions

With Energy Absorbing Swivel Attachment Point
15kN Rated/Single Person Use
Universal Plate

Test Type

Dynamic & Static Test to AS/NZS 5532:2013

Roof Sheet Type

Custom Orb

Roof Sheet (BMT)

0.42mm

Purlin Spacing

1500mm

Anchor Load Limit

15kN Ultimate Load (Single Person Free Fall Arrest)

Minimum Fixings

8x Bulbrite 7.7x27.7 Aluminium Rivets, 2x 14gx75 Roof Screws

This item also meets requirements using 2x12gx45 Roof Zips Screws

Date Certificate Is Prepared

01/10/2014

DISCLAIMER

Product designed as a single point anchor device used for harness based work. Any change made to the roof deck design, material composition or installation method will void this certification. All Safemaster products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Safemaster requirements or the use of non Safemaster components will void all certification and warranties. Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a structural engineer or a site specific live load test done to ensure conformance. Maintenance and usage of the system in accordance with Safemaster requirements is the responsibility of the owner or manager of the workplace. Safemaster takes no responsibility for the misuse of or tampering with this Height Safety Equipment or its use by untrained personnel.

TEST CERTIFICATE

ANCHOR POINT PERFORMANCE



Safemaster certifies that **X-ERT Surface Mount Anchor Kit (Code: APS205)** is designed, manufactured and tested in accordance with **AS/NZS 5532:2013** subject to installation of roof deck and anchor point in accordance with manufacturer's requirements



Test Identification

140/143

Tested Item

APS205 - X-ERT Surface Mount Anchor

Tested Item Descriptions

With Energy Absorbing Swivel Attachment Point
15kN Rated/Single Person Use
Universal Plate

Test Type

Dynamic test to AS/NZS 5532:2013

Roof Sheet Type

Sandwich Panel

Roof Sheet (BMT)

0.42mm

Purlin Spacing

2400mm

Anchor Load Limit

15kN Ultimate Load (Single Person Free Fall Arrest)

Minimum Fixings

10x Bulbtite 7.7x27.7 Aluminium Rivets

Date Certificate Is Prepared

21/09/2014

DISCLAIMER

Product designed as a single point anchor device used for harness based work. Any change made to the roof deck design, material composition or installation method will void this certification. All Safemaster products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Safemaster requirements or the use of non Safemaster components will void all certification and warranties. Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a structural engineer or a site specific live load test done to ensure conformance. Maintenance and usage of the system in accordance with Safemaster requirements is the responsibility of the owner or manager of the workplace. Safemaster takes no responsibility for the misuse of or tampering with this Height Safety Equipment or its use by untrained personnel.

TEST CERTIFICATE

ANCHOR POINT PERFORMANCE



Safemaster certifies that **X-ERT Surface Mount Anchor Kit (Code: APS205)** is designed, manufactured and tested in accordance with **AS/NZS 5532:2013** subject to installation of roof deck and anchor point in accordance with manufacturer's requirements



Test Identification

131/137

Tested Item

APS205 - X-ERT Surface Mount Anchor

Tested Item Descriptions

With Energy Absorbing Swivel Attachment Point
15kN Rated/Single Person Use
Universal Plate

Test Type

Dynamic & Static Test to AS/NZS 5532:2013

Roof Sheet Type

Trimdek

Roof Sheet (BMT)

0.42mm

Purlin Spacing

1500mm

Anchor Load Limit

15kN Ultimate Load (Single Person Free Fall Arrest)

Minimum Fixings

8x Bulbtite 7.7x27.7 Aluminium Rivets, 2x 14gx75 Roof Screws

This item also meets requirements using 2x12gx45 Roof Zips Screws

Date Certificate Is Prepared

12/09/2014

DISCLAIMER

Product designed as a single point anchor device used for harness based work. Any change made to the roof deck design, material composition or installation method will void this certification. All Safemaster products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Safemaster requirements or the use of non Safemaster components will void all certification and warranties. Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a structural engineer or a site specific live load test done to ensure conformance. Maintenance and usage of the system in accordance with Safemaster requirements is the responsibility of the owner or manager of the workplace. Safemaster takes no responsibility for the misuse of or tampering with this Height Safety Equipment or its use by untrained personnel.

TEST CERTIFICATE

ANCHOR POINT PERFORMANCE



Safemaster certifies that **X-ERT Surface Mount Anchor Kit (Code: APS205)** is designed, manufactured and tested in accordance with **AS/NZS 5532:2013** subject to installation of roof deck and anchor point in accordance with manufacturer's requirements



Test Identification

131/137

Tested Item

APS205 - X-ERT Surface Mount Anchor

Tested Item Descriptions

With Energy Absorbing Swivel Attachment Point
15kN Rated/Single Person Use
Universal Plate

Test Type

Dynamic & Static Test to AS/NZS 5532:2013

Roof Sheet Type

Spandek

Roof Sheet (BMT)

0.42mm

Purlin Spacing

1500mm

Anchor Load Limit

15kN Ultimate Load (Single Person Free Fall Arrest)

Minimum Fixings

8x Bulbrite 7.7x27.7 Aluminium Rivets, 2x 14gx75 Roof Screws

This item also meets requirements using 2x12gx45 Roof Zips Screws

Date Certificate Is Prepared

12/09/2014

DISCLAIMER

Product designed as a single point anchor device used for harness based work. Any change made to the roof deck design, material composition or installation method will void this certification. All Safemaster products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Safemaster requirements or the use of non Safemaster components will void all certification and warranties. Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a structural engineer or a site specific live load test done to ensure conformance. Maintenance and usage of the system in accordance with Safemaster requirements is the responsibility of the owner or manager of the workplace. Safemaster takes no responsibility for the misuse of or tampering with this Height Safety Equipment or its use by untrained personnel.

TEST CERTIFICATE

ANCHOR POINT PERFORMANCE



Safemaster certifies that **X-ERT Surface Mount Anchor Kit (Code: APS205)** is designed, manufactured and tested in accordance with **AS/NZS 5532:2013** subject to installation of roof deck and anchor point in accordance with manufacturer's requirements



Test Identification

068/033

Tested Item

APS205 - X-ERT Surface Mount Anchor

Tested Item Descriptions

With Energy Absorbing Swivel Attachment Point
15kN Rated/Single Person Use
Universal Plate

Test Type

Dynamic & Static Test to AS/NZS 5532:2013

Roof Sheet Type

King Clip 700

Roof Sheet (BMT)

0.42mm

Purlin Spacing

1500mm

Anchor Load Limit

15kN Ultimate Load (Single Person Free Fall Arrest)

Minimum Fixings

7x Bulbtite 7.7x27.7 Aluminium Rivets, 2x 14g 10x75mm Screws

Date Certificate Is Prepared

18/09/2014

DISCLAIMER

Product designed as a single point anchor device used for harness based work. Any change made to the roof deck design, material composition or installation method will void this certification. All Safemaster products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Safemaster requirements or the use of non Safemaster components will void all certification and warranties. Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a structural engineer or a site specific live load test done to ensure conformance. Maintenance and usage of the system in accordance with Safemaster requirements is the responsibility of the owner or manager of the workplace. Safemaster takes no responsibility for the misuse of or tampering with this Height Safety Equipment or its use by untrained personnel.